

System Configuration	
Intel [®] Processor	Intel Mobile Core i3-3217U CPU, 1.8GHz, 3M cache
Memory	DDR3L 1333/1600MHz SO-DIMM x 1, Default 4GB, Max. 8GB
Storage	SATA 2.5" Hard Drives (HDD) / Flash Storage (SSD) / mSATA SSD
Power supply	DC12V/6A External Power Adapter. AC100 to 240V Full Range.
O/S compatibility	Windows XP, POS Ready 2009, Windows 7, POS Ready 7, Windows 10 IoT, Linux
System Dimensions (WxHxD)	Width: 245mm / Height: 48mm /Depth: 195mm
System Weight (with stand)	1.6Kg
Package Dimensions (L*W*H)	360(L) x 280(W) x 145(H) mm / 2.5KG
Wall Mount	VESA 100x100mm Compliant
Product Certification	CE / FCC / ROHS / BSMI / BIS
Operation Temperature	0°C ~ 40°C
Storage Temperature	-25°C ~ 70°C
Humidity	15% ~ 80%
I/O Connectivity	
Parallel	1 Port DB-25 Printer Port (Standard)
USB	6 Ports, 6 x USB 2.0
LAN	1 Port RJ-45 LAN with activity and link LEDs 10/100/1000 Gb Ethernet
SERIAL	4 x DB-9, COM 1~ COM 4
Cash DRAWER	1 Port RJ11 / Support 1 Cash Drawer (12V)
AUDIO	3W Speaker, 1 x Line out, 1 x MIC in
VGA	1 Port DB-15
PS/2	1 Port PS/2 KB
DC12V out Jack	1 port DC + 12v/1A for P2+ Monitor
Extension Slot	mini-PCI-e slot x 1
Option	
2nd Monitor	15" LCD Panel, 1024 x 768, Flat Type, PCAP (Option: Touch Function), VGA interface, 9.7" LED Panel, 1024 x 768, Bezel Type, with 5W Resistive (Option: Touch Function), VGA interface
Customer Display	CD-230 : 9mm, 20 x 2, USB Interface CD-300 : Graphics mode, Multi-language, USB Interface
HDMI Port	HDMI x 1 (via VGA to HDMI Converter)
2nd VGA Port	By Factory Setup (Either VGA-2 or COM 4)
WiFi	WiFi 802.11 b/g/n
Wall Mount	VESA 100 x 100mm