

System Configuration	
Processor	Intel Bay Trail Quad Core Celeron J1900, 2GHz up to 2.42GHz, 2M cache
Memory	DDR3L 1333 SO-DIMM x 1, Default 2GB, Max. 8GB
Storage	SATA 2.5" Hard Drives (HDD) / Flash Storage (SSD) / mSATA SSD
Power supply	DC12V/5A External Power Adapter. AC100 to 240V Full Range.
O/S compatibility	Windows 7, POS Ready 7, Windows 10 IoT, Linux
Physical Dimensions (W*H*D)	Width: 372mm / Height: 310mm (Full Extended); 280mm (Low-Profile);127mm (Folded-Flat) / Stand Depth: 250mm
System Weight (with stand)	6.1Kg / 3.6Kg(without stand)
Package Dimensions	505(L) x 445(W) x 230(H) mm / 8.2KG
Wall Mount	VESA 100x100mm compliant
Product certification	CE / FCC / ROHS / BSMI / BIS
Operation Temperature	0°C ~ 40°C
Storage Temperature	-25°C ~ 70°C
Humidity	15% ~ 80%
LCD & Touch Panel	
Display	15" LED-backlight display
Brightness	250 cd/m2
Resolution	1024x768 (default)
Touch	Bezel Type Resistive Touch / Flat Type Resistive Touch / Flat Type Projected Capacitive Touch (PCAP), USB Interface
I/O Connectivity	
Parallel	1 port DB-25 Printer Port (Standard)
USB	5 ports, 5 x USB 2.0
LAN	1 Port RJ-45 LAN with activity and link LEDs 10/100/1000 Gb Ethernet
SERIAL	4 x DB-9, COM 1 & COM 3 Support 5V / 12V By Jumper
Cash DRAWER	1 Port RJ11 / Support 1 Cash Drawer (12V)
AUDIO	3W Speaker, 1 x Line out, 1 x MIC in
VGA	1 port DB-15
PS/2	1 port PS/2 KB
DC12V out Jack	1 port DC + 12v/1A for P2 + Monitor
Extension Slot	mini-PCI-e slot x 1
Option	
2nd Display	15" LCD Panel, 1024 x 768, Flat Type, PCAP (Option: Touch Function), VGA interface, 9.7" LED Panel, 1024 x 768, Bezel Type, with 5W Resistive (Option: Touch Function), VGA interface
MSR	2 or 3 Tracks, USB Interface
Customer Display	CD-230 : 9mm, 20 x 2, USB Interface CD-300 : Graphics mode, Multi-language, USB Interface
WiFi	Wi-Fi 802.11 b/g/n.
RAID Card	RAID 1 Mode, 2nd HDD or SSD
Wall Mount Kits	VESA 100 x 100mm