

LU950 Installation Projector

Display

Projection System **DLP Single 0.47" WUXGA**

DMD type **DC3 DMD Chip**

Resolution **1920x1200 pixels**

Brightness **5000 ANSI Lumens**

Contrast Ratio* **3,000,000:1**

Display Color **30 Bits (1.07 billion colors)**

Aspect Ratio **Native 16:10 (5 aspect ratio selectable)**

Light Source **Laser**

Light Source Life* **20,000 hrs**

Optical

Throw Ratio **1.36 ~ 2.18**

Zoom Ratio **1.6x**

Lens Control **Manual Zoom and Focus**

Lens Shift **Manual lens shift,
V: ±60 %; H: ±23 %**

Keystone Correction **2D keystone,
V: ±30 degree; H: ±30 degree**

Projection Size **30" ~ 300"**

Audio

Built-in Speaker **10W**

Special Feature

Security(anti-theft) **Security Bar**

Feature **Digital Shrink and Shift, Image
Memory, Projector/ Remote
Control ID Setting, Auto High**

Altitude Mode, HDBaseT, LAN Control, 360° Projection, Dust-Proof Filter

Compatibility

Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking"
---------------------------	--

Horizontal Frequency	15~102KHz
-----------------------------	------------------

Vertical Scan Rate	24 ~ 120 Hz
---------------------------	--------------------

HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
---------------------------	---

Video Compatibility	NTSC, PAL, SECAM
----------------------------	-------------------------

Power

Power Consumption (Max/Normal/Eco)	Max 530W/ Normal 475W/ Eco 365W
---	--

Standby Power Consumption	Normal < 0.5W, Network <2W
----------------------------------	---

Power Supply	100 ~ 240V AC
---------------------	----------------------

Dimension and Weight

**Product Dimensions
(WxHxD)** **490 mm x 159 mm x 380 mm**

Product Weight **9.4 kg**

Operation Condition

**Noise Level
(Normal/Eco)** **37 /35 dBA**

**Operating
Temperature** **0 ~ 40° C**

Accessories

**Accessories
(Standard)** **Power Cord
Remote control (RCA011)
Lens cover
AAA Batteryx2
Installation Guide/Regulatory
Statement(Combined)
Warranty card(by sku)
Anti-dust Filter**

**Accessories
(Optional)** **Ceiling mount (CMG3)
3D glasses
InstaShow™ (WDC10)**

Connectivity

I/O Port

Wired Remote In x1
RS232 In (D-sub 9pin, male) x1
USB Mini-B(Service) x1
USB TypeA(5V/2A power) x1
LAN Port(RJ45 for Network control) x1
HDBaseT x1
HDMI In x3
HDMI Out x1
S-Video in x1
Composite Video(RCA) x1
RCA Audio in- L/R x1
PC In x1
Monitor out (D-sub 15pin,Female) x1
Audio in(mini jack) x1
Audio out (mini jack) x1
12V Trigger x1
IR Receiver(Front) x1
IR Receiver(Rear) x1