

General Information

Technical Specifications

Technology	Kyocera TASKalfa Laser MFP
Control Panel Type	10.1" Color TSI
Product Category	A3 Color MFP
Functions (Print / Scan / Copy / Fax)	Print/Scan/Copy/Fax
Engine Speed	32 ppm B&W, 32 ppm Color
Warm-up Time	18 Seconds
First Page Out Time (print/copy)	Print: 5.9 Seconds B&W, 7.7 Seconds Color Copy: 5.3 Seconds B&W, 7.0 Seconds Color
Resolution	1200 x 1200 dpi
Bit Depth	8 Bit
CPU	Freescale QorIQ T1024 (Dual Core) / 1.0GHz
Memory (std/max)	Standard: 4 GB RAM Maximum: 4 GB RAM
Hard Disk Drive (Standard / Optional)	Standard: 320 GB HDD and 8 GB SSD
Electrical Requirements	120V: 60Hz, 12A; 220-240V: 50Hz, 7.2A
Dimensions (W x D x H)	60.2 cm x 66.5 cm x 79 cm
Mainframe Weight	198.4 lbs
Maximum Monthly Duty Cycle	125,000 Pages Per Month

Maximum average monthly print volume	N/A
Power Consumption	Typical Electricity Consumption (TEC): 120V: 1.53 kWh/week; 220V: 1.46 kWh/week
Input Capacity (std/max)	Standard: 1,150 Sheets Maximum: 7,150 Sheets
Output Capacity (std / max)	Standard: 500 Sheets Maximum: 4,000 Sheets
Paper Sources (std / max)	Standard: 2 Trays + 1 MPT Maximum: 5 Trays + 1 MPT
Maximum Paper Size	12" x 48"
Supported Paper Weights	Trays/MPT: 14 lb Bond - 166 lb Index
Input Materials	Plain, Bond, Recycled, Preprinted, Vellum, Color, Pre-Punched, Thick, Thin, High Quality, Letterhead, Envelope, Custom
Standard Interface	10/100/1000BaseTX, Hi-Speed USB 2.0, 4 USB Host Interfaces, 2 Expansion Slots