

SPECIFICATIONS

LCD

Type: 21.5" Wide
Display Area: 21.5 inch
Optimum Resolution: 1920x1080
Contrast Ratio: 1,000:1 (typical), 20,000,000 : 1 (DCR)
Brightness: 200 cd/m² (typ)
Viewing Angles: 170° / 160° (typ.)
Response Time: 5ms
Panel Surface: 8H Hardness
Light Source: 40,000 Hrs (Min.)

VIDEO INPUT

Analog: RGB Analog (75Ω, 0.7 / 1.0 Vp-p)
Digital: DVI-D (TMDS, 100Ω)
Frequency: Fh: 24-83KHz; Fv: 50-76Hz
Sync: Separate Sync / Composite Sync / SOG

COMPATIBILITY

PC: VGA up to 1920 x 1080
Mac: MAC up to 1920 x 1080 (Touch function not compatible)

CONNECTOR

Analog: D-sub *1
Digital: DVI *1
USB: Up Stream: Type B *1
Down Stream: Type A *2
Power: Internal Power Board, 3-pin Plug (CEE22) *1

POWER

Voltage: AC 100–240V (universal), 50 / 60Hz
Consumption: (ECO Mode)Standard: 26W; Optimize: 21W; Conserve: 18W

OPERATING CONDITIONS

Temperature: 0° ~ 40° C / 32° ~ 104° F
Humidity: 20%-90% (non-condensing)

DIMENSIONS

Physical: 511mm (width) x 365mm (height) x 240mm (depth)

WEIGHT

Net: 4.9 kg

REGULATIONS

CE, CB, BSMI, PSB, SASO, C-tick, e-standby, KC, UL/cUL,
FCC-B (including ICES003), UL CoC, Mexico Energy,
GOST-R/Hygienic, UkrSEPRO, TCO 5.2, Erp, CCC, China
Energy, ENERGY STAR®, EPEAT Silver, WEEE, RoHS,
SVHC list

WALL MOUNT

100mm x 100mm

PACKAGE CONTENTS

TD2220-2 display, power cable, AC/DC adapter, USB Cable, VGA cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD (available in some countries only)
