

Overview

Model Name APC Power-Saving Back-UPS 700VA, 230V, BS1363

Includes CD with software , Telephone Cable , User Manual

Standard Lead Time Usually in Stock

Product Distribution Botswana , Gambia , Ghana , Hong Kong , Ireland , Kenya , Malawi , Malta , Nigeria , Saudi Arabia , Sierra Leone , TANZANIA, UNITED REPUBLIC OF , United Arab Emirates , Yemen , Zambia , Zimbabwe

Output

Output Power Capacity 405 Watts / 700 VA

Max Configurable Power (Watts) 405 Watts / 700 VA

Nominal Output Voltage 230V

Output Frequency (sync to mains) 47 - 63 Hz

Standby

Waveform Type Stepped approximation to a sinewave

Output Connections (4) BS 1363 (Battery Backup) , (4) BS 1363 (Surge Protection)

Output Voltage Tolerance +/- 5% static and 100% load step

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 5 Hz (auto sensing)

Input Connections British BS1363A

Cord Length 1.83 meters

Input voltage range for main operations 180 - 266 V

Maximum Input Current 10 A

Input Breaker Capacity 10 A

Batteries & Runtime

Battery Type Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof

Typical recharge time 16 hour(s)

Replacement Battery	RBC17
Communications & Management	
Interface Port(s)	USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Surge Protection and Filtering	
Surge energy rating	310 Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-45 connector) , Network line - 10/100 Base-T Ethernet (RJ-45 connector)
Physical	
Maximum Height	89.0 mm
Maximum Width	224.0 mm
Maximum Depth	311.0 mm
Net Weight	6.93 kg
Shipping Weight	7.84 kg
Shipping Height	127.0 mm
Shipping Width	279.0 mm
Shipping Depth	400.0 mm
Master Carton Units	2.0
Master Carton Dimensions (Length x Width x Height)	12.75 inches
Master Carton Weight	16.36 kg
Color	Black
SCC Codes	1073130426834 2
Units per Pallet	48.0
Pallet Dimensions	1220.0 mm

# of Layers per Pallet	4
# of Units per Layer per Pallet	20
Pallet Weight	636.36 kg
Environmental	
Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-9000 meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-9000 meters
Audible noise at 1 meter from surface of unit	40.000 dB
Conformance	
Approvals	CE
Standard warranty	2 years repair or replace , 3 years repair or replace for European Union countries
Equipment protection policy	Lifetime : 50000 GBP
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs