
DISPLAY SIZE (IN.)

24

RESOLUTION

1920 x 1080

STATIC CONTRAST RATIO

3,000:1

RESPONSE TIME (TYPICAL GTG)25ms

DISPLAY

DISPLAY SIZE (IN.)

24

VIEWABLE AREA (IN.)

23.6

RESOLUTION

1920 x 1080

STATIC CONTRAST RATIO

3,000:1

DYNAMIC CONTRAST RATIO

50,000,000:1

BRIGHTNESS

250 cd/m2

BACKLIGHT LIFE (HOURS)

40,000

RESPONSE TIME (TYPICAL GTG)

25ms

PANEL TYPE

MVA

COLORS

16.7M

VIEWING ANGLES

178° horizontal, 178° vertical

LIGHT SOURCE

LED

PANEL SURFACE

7H Scratch Resistant Surface Hardness

ASPECT RATIO16:9

COMPATIBILITY

PC RESOLUTION (MAX)1920 x 1080

TOUCH

TOUCH TECHNOLOGY	TOUCH POINTS
Projective Capacitive	10-Point Touch

CONNECTOR

USB 3.0 TYPE A	USB 3.0 TYPE B
2	1
VGA	HDMI 1.4
1	1
DISPLAY PORT	
1	

AUDIO

INTERNAL SPEAKERS
2.5W (x2)

VIDEO SIGNAL

FREQUENCY HORIZONTAL	FREQUENCY VERTICAL
Analog: 24 ~ 82Hz, Digital: 15 ~ 82Hz	Analog: 50 ~ 75Hz, Digital: 24 ~ 75Hz

VIDEO INPUT

ANALOG SYNC

Separate Sync / Composite Sync / Sync on
Green, TMDS, PCI-E

POWER

ECO MODE (CONSERVE)

19W

ECO MODE (OPTIMIZED)

22W

CONSUMPTION (TYPICAL)

25W

CONSUMPTION (MAX)

28W

VOLTAGE

AC 100-240V (universal), 50-60Hz

STAND-BY

0.5W

CONTROLS

PHYSICAL CONTROLS

1, 2, Up, Down, Power

ON SCREEN DISPLAY

Auto Image Adjust, Contrast/Brightness,
Input Select, Audio Adjust, Color Adjust,
Information, Manual Image Adjust, Advanced
Image Adjust, Setup Menu, Memory Recall
(See user guide for complete OSD
functionality)

OPERATING CONDITIONS

TEMPERATURE

32-104° F (0 - 40° C)

HUMIDITY (NON-CONDENSING)

20-90%

ERGONOMICS

TILT (FORWARD/BACK)

20° - 53°, 90° (Flat)

ADDITIONAL HARDWARE

KENSINGTON LOCK SLOT

1

MOUNT

VESA COMPATIBLE

100 x 100 mm

WEIGHT (METRIC)

GROSS (KG)

7.1

NET WITHOUT STAND (KG)

5.5

WEIGHT (IMPERIAL)

NET (LBS)

12.2

GROSS (LBS)

15.6

DIMENSIONS (METRIC) (WXHxD)

PACKAGING (MM)

643 x 435 x 140

PHYSICAL (MM)

573 x 353 x 47

DIMENSIONS (IMPERIAL) (WXHxD)

PACKAGING (IN.)

25.3 x 17.1 x 5.5

PHYSICAL (IN.)

22.6 x 13.9 x 1.9
