

SPECIFICATIONS

LCD PANEL

Monitor Size: 32"W (31.5" Viewable)
Panel Technology: SuperClear® IPS TFT CD
Resolution: 1920 x 1080
Display Area: 698.4mm (H) x 392.85mm (V)
Aspect Ratio: 16:9
Brightness: 250 cd/m2 (Typ)
Contrast Ratio: 1200:1 (Typ)
Dynamic Contrast Ratio: 80,000,000:1
Viewing Angle: 178 degrees / 178 degrees (Typ)
Response Time: 4 ms (GtG)
Colour Gamut: 75% of NTSC (Typ)
Panel Surface: Anti-Glare (semi-glossy) type, Haze 1%
Pixel Pitch: 0.364mm (H) x 0.364mm (V)

INPUT SIGNAL

Frequency: VGA: Fh = 24 ~ 83KHz ; Fv = 50 ~ 75Hz
HDMI: Fh = 24 ~ 83KHz ; Fv = 50 ~ 75Hz
DisplayPort: Fh = 24 ~ 83KHz ; Fv = 50 ~ 75Hz
Sync: VGA: Separate Sync
HDMI: TMDS
DisplayPort: PCI-E

COMPATIBILITY

PC: Windows 7, Windows 8, Windows 8.1, Windows 10 certified
Mac®: Power Mac tested

CONNECTOR

Digital: HDMI x 1 (v1.4 compatible)
DisplayPort x 1 (v1.2 compatible)
Analog: VGA x 1
Audio Out: Earphone out x 1 (3.5mm plug)
Audio In: Audio in x 1 (3.5mm plug)

SPEAKERS

2W x 2

POWER

Power: 3-pin plug (CEE22) x 1
Voltage: AC 100-240V (Universal); 50/60Hz
Consumption: 36W
Optimize: 31W
Conserve: 26W

ERGONOMICS

Tilt: 15 ~ -4 degrees

SPECIAL FEATURES

DDC/2B, DDC/CI, HDCP, Detachable Base, KENSINGTON Microsaver Security Compatible

WALL MOUNT

VESA®: 100mm x 100mm

OPERATING CONDITIONS

Temperature (° F / ° C): 32°F to 104°F (0°C to 40°C)

Humidity: 20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm): 712.89mm (W) x 503.87mm (H) x 230mm (D)

Physical without stand (mm): 712.89mm (W) x 416.4mm (H) x 38.2mm (D)

Packaging (mm): 785mm (W) x 498mm (H) x 112mm (D)

WEIGHT

Net with stand (kg): 6.2kg

Net without stand (kg): 5.6kg

Gross (kg): 8.2kg

REGULATIONS

CE, REACH, WEEE, EEL, CU/EAC, UkrSEPRO, BSMI, RCM, GEMS, KC, BIS

PACKAGE CONTENTS

LCD Display

Power Cable

HDMI Cable

Quick Start Guide

*Actual content may differ from market to market
