

Specification

Zebra ZD410 - label printer - monochrome - direct thermal

| | |
|------------------------------|--|
| Printer Type | Label printer - direct thermal - monochrome |
| Weight | 1 kg |
| Localisation | United Kingdom, Europe |
| Max Media Size | Roll (6 cm) |
| Print Speed | Up to 152 mm/sec - B/W |
| Max Resolution (B&W) | 203 dpi |
| Interface | USB 2.0, USB host, Bluetooth 4.0 |
| RAM Installed (Max) | 256 MB SDRAM |
| Flash Memory Installed (Max) | 512 MB |
| Language Simulation | ZPL II, EPL2, ZBI |
| Barcodes | Code 93, Industrial 2 of 5, Code 39, Code 49, CODABLOCK, ISBT 128, QR code, MaxiCode, Aztec code, LOGMARS, UPC-A, UPC-E, MicroPDF417, Codabar, Code 128, Code 11, Interleaved 2 of 5, Postnet, PDF417, Data Matrix, PLANET, Plessey, Standard 2 of 5, EAN-8, EAN-13, MSI |
| Media Type | Receipt paper, tag stock, continuous paper labels, die cut labels, wristband labels, fanfold labels |
| Features | Black Mark sensor, transmissive media sensor, reflective media sensor, tear bar |
| Power | AC 120/230 V |
| Dimensions (WxDxH) | 11.5 cm x 22 cm x 15.1 cm |

Extended Specification

General

| | |
|--------------|---|
| Localisation | United Kingdom, Europe |
| Printer Type | Label printer - direct thermal - monochrome |

Dimensions & Weight

| | |
|--------|---------|
| Depth | 22 cm |
| Height | 15.1 cm |
| Weight | 1 kg |
| Width | 11.5 cm |

Environmental Parameters

| | |
|---------------------------|---------------------------|
| Humidity Range Operating | 10 - 90% (non-condensing) |
| Max Operating Temperature | 41 °C |

Environmental Parameters

Min Operating Temperature 4.4 °C

Environmental Standards

ENERGY STAR Yes

Expansion / Connectivity

Connections 1 x USB 2.0 - 4 pin USB Type B | 1 x USB host - 4 pin USB Type A

Flash Memory

Flash Memory 512 MB

Media Handling

Max Media Size Roll (6 cm)

Max Printing Length 991 mm

Max Printing Width 56 mm

Media Feeders 1 x manual - 1 roll - Roll (6 cm)

Media Sizes Roll (6 cm)

Media Thickness Range 0.08 mm - 0.305 mm

Media Type Receipt paper, tag stock, continuous paper labels, die cut labels, wristband labels, fanfold labels

Roll Core Diameter 25.4 mm, 76.2 mm, 38.1 mm, 12.7 mm, 50.8 mm

Roll Maximum Outer Diameter 127 mm

Miscellaneous

Compliant Standards FCC Class B certified, VCCI, C-Tick, BSMI, ICES-003, NOM, SABS, EN55024, EN55022 Class B, FCC Part 15.247, CCC, IC, IEC 60950-1, KCC, EN 301.893, FCC Part 15.209, S Mark, cTUVus, EN 62311, EN 300 328, BIS, INMETRO, EN61000-3-2, EN61000-3-3, CU, RSS-247

Power

Frequency Required 50/60 Hz

Power Device Power supply

Power Factor Correction Yes

Voltage Required AC 120/230 V

Printer

Printer

Barcodes Code 93, Industrial 2 of 5, Code 39, Code 49, CODABLOCK, ISBT 128, QR code, MaxiCode, Aztec code, LOGMARS, UPC-A, UPC-E, MicroPDF417, Codabar, Code 128, Code 11, Interleaved 2 of 5, Postnet, PDF417, Data Matrix, PLANET, Plessey, Standard 2 of 5, EAN-8, EAN-13, MSI

Connectivity Technology Wireless

Features Black Mark sensor, transmissive media sensor, reflective media sensor, tear bar

Fonts Included 16 x bitmapped ZPL II | 2 x scalable ZPL | 5 x expandable EPL2

Interface USB 2.0, USB host, Bluetooth 4.0

Language Simulation ZPL II, EPL2, ZBI

Max Resolution (B&W) 203 dpi

Print Speed Up to 152 mm/sec - B/W - 203 dpi

RAM

RAM Installed (Max) 256 MB

Technology / Form Factor SDRAM

Software / System Requirements

Software Included Drivers & Utilities