

## DS9208 Specifications

### PHYSICAL CHARACTERISTICS

<b>Dimensions</b>	5.512 in. H x 3.232 in. W x 3.150 in. D 14.0 cm H x 8.21 cm W x 8.0 cm D
<b>Weight</b>	9.5 oz./269 g
<b>Voltage and Current</b>	Idle: 5 ± 10% VDC @ 150ma average Scanning: 5 ± 10% VDC @ 230ma average
<b>Color</b>	Midnight Black

### USER ENVIRONMENT

<b>Operating Temp.</b>	32° F to 104° F / 0° to 40° C
<b>Drop Specs</b>	Withstands multiple 5 ft./1.5 m drops to concrete
<b>Humidity</b>	5% to 85% RH (non-condensing)
<b>Ambient Light Immunity</b>	Immune to natural and artificial ambient light (i.e. sunlight, incandescent, fluorescent, mercury vapor, sodium vapor)

### SYMBOLGY DECODE CAPABILITY

<b>1D</b>	UPC/EAN (UPCA/UPCE/UPCE1/EAN-8/EAN-13/JAN-8/JAN-13 plus supplementals, ISBN (Bookland), ISSN, Coupon Code), Code 39 (Standard, Full ASCII, Trioptic, Code 32 (Italian Pharmacode), Code 128 (Standard, Full ASCII, UCC/EAN-128, ISBT-128 Concatenated), Code 93, Codabar/NW7, 2 of 5 (Interleaved 2 of 5, Discrete 2 of 5, IATA, Chinese 2 of 5, Matrix 2 of 5, Code 11), MSI Plessey, GS1 DataBar Omnidirectional, Truncated, Stacked, Stacked Omnidirectional, Limited, Expanded, Expanded Stacked)
<b>PDF417 (and variants)</b>	PDF417 (Standard, Macro), MicroPDF417 (Standard, Macro), Composite Codes (CC-A, CC-B, CC-C)
<b>2D</b>	TLC-39, Aztec (Standard, Inverse), MaxiCode, DataMatrix/ECC 200 (Standard, Inverse), QR Code (Standard, Inverse, Micro)
<b>Postal</b>	U.S. Postnet and Planet, U.K. Post, Japan Post, Australian Post, Netherlands KIX Code, Royal Mail 4 State Customer, UPU FICS 4 State Postal, USPS 4CB, Canadian Post (Postbar)
<b>Nominal Working Range</b>	<b>Code 39 – 5 mil:</b> 0 – 4.5 in. (0 – 11.4 cm) <b>UPC/EAN – 10 mil (80%):</b> 0 – 8.5 in. (0 – 21.6 cm) <b>UPC/EAN – 13 mil (100%):</b> 0 – 10.5 in. (0 – 26.7 cm) <b>PDF417 – 6.6 mil:</b> 0 – 3.8 in. (0 – 9.6 cm) <b>Datamatrix – 10 mil:</b> 0 – 4.7 in. (0 – 11.9 cm)
<b>Minimum Resolution</b>	Code 39 – 4 mil UPC – 7.8 mil (60%) PDF417 – 5 mil

<b>Swipe Speed (Vertical Read Rate)</b>	Up to 90 in./2.3 m per second
---	-------------------------------

### IMAGING CHARACTERISTICS

<b>Graphics Format Support</b>	Images can be exported as Bitmap, JPEG or TIFF
<b>Image Transfer Speed</b>	USB 2.0: Up to 12 Megabits/second RS-232: Up to 115 kb/second
<b>Image Transfer Time</b>	Typical USB application is ~0.2 seconds with a compressed JPEG of 100kb
<b>Image Quality</b>	120 PPI on a 4 x 6 in./10.2 x 15.2 cm document @ 4.7 in./11.9 cm

### REGULATORY

<b>Electrical Safety</b>	UL6950-1, CSA C22.2 No. 60950-1:2nd ed., EN60950-1: 2nd ed. + A1: 2009 IEC60950-1: 2nd ed.
<b>LED Safety</b>	IEC / EN 60825-1: 2001 Class 1M LED, EN 62471: 2008 IEC 62471: 2006
<b>EMI/RFI</b>	FCC CFR47 Part 15 Class B: 2007, ICES-003 Issue 4: 2004 Class B, EN 55022: 2006 + A1: 2007, EN 55024: 1998 + A1: 2001 + A2: 2003 AS/NZS CISPR22:2006, VCCI:2007
<b>Environmental</b>	Compliant with RoHS Directive 2002/95/EC

### INTERFACES

<b>Interfaces Supported</b>	USB, RS-232, RS-485 (IBM 46xx Protocols), Keyboard Wedge
-----------------------------	--

### WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the DS9208 is warranted against defects in workmanship and materials for a period of 3 years from the date of shipment. For the complete Zebra hardware product warranty statement, go to [www.zebra.com/warranty](http://www.zebra.com/warranty)

### Ideal For These Applications:

#### Industries

- Retail
- Hospitality