

Specifications

Print speed black (ISO, A4)	Up to 61 ppm
First page out black (A4, ready)	As fast as 5.4 sec
Duty cycle (monthly, A4)	Up to 275,000 pages
Recommended monthly page volume	5,000 to 25,000 ³
Print technology	Laser
Print quality black (best)	Up to 1200 x 1200 dpi
Display	6.86 cm (2.7 in) QVGA LCD (colour graphics), rotating (adjustable angle)
Mobile printing capability	HP ePrint Apple AirPrint™ Mopria-certified
Wireless capability	Optional, enabled with purchase of HP Jetdirect 2900nw Print Server J8031A or HP Jetdirect 3000w NFC/Wireless Accessory J8030A
Connectivity, standard	1 Hi-Speed Device USB 2.0 2 Hi-Speed USB 2.0 Host 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network Hardware Integration Pocket
Compatible Operating Systems	Android, Linux Boss (5.0), Linux Debian (7.0, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, 7.8, 7.9, 8.0, 8.1, 8.2, 8.3, 8.4, 8.5, 8.6), Linux Fedora (22, 23, 24), Linux Mint (17, 17.1, 17.2, 17.3, 18), Linux Red Hat Enterprise (6.0, 7.0), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.11 El Capitan, OS X 10.10 Yosemite, UNIX, Windows 10 all 32/64-bit editions (excluding RT OS for Tablets), Windows 7 all 32/64-bit editions, Windows 8/8.1 all 32/64-bit editions (excluding RT OS for Tablets), Windows Vista all 32-bit editions (Home Basic, Premium, Professional, etc.), Windows XP SP3 32-bit editions (XP Home, XP Pro, etc.)
Memory	512 MB
Maximum Memory	1.5 GB, MAX memory, when 1 GB Accessory DIMM is installed
Internal Storage	Optional, 500 GB (with accessory B5L29A)
Paper handling input, standard	100-sheet multipurpose feeder, 550-sheet input feeder
Paper handling input, optional	Optional 1 x 550-sheet paper feeder, optional 1 x 550 paper feeder and stand with cabinet, optional 3 x 550-sheet paper feeder and stand, optional high-capacity paper feeder and stand with 1 x 550 sheet feeder and 1 x 2,000-sheet feeder
Paper handling output, standard	500 sheet output bin
Paper handling output, optional	Optional 5 bin stapler stacker
Duplex printing	Automatic (standard)
Finished output handling	Sheetfed
Media sizes supported	Feeder 1: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), 10 x 15 cm, Oficio (216 x 340 mm), 16K, envelopes (C5, B5, C6, DL ISO), Postcard (JIS single and double) Feeder 2: A4, A5, A5-R, B5 (JIS), 16K
Media types	Paper (plain, light, bond, recycled, heavy, extra heavy, cardstock, pre-

	printed, pre-punched, coloured, rough, heavy rough), monochrome transparency, labels, letterhead, envelope, heavy envelope
Energy efficiency	ENERGY STAR® qualified EPEAT® Silver EPEAT® Gold (#AAZ, #201 options only)
Blue Angel compliant	Yes, Blue Angel DE-UZ 205—only ensured when using Original HP supplies
Operating temperature range	10 to 32.5°C
Recommended operating humidity range	30 to 70% RH
Minimum dimensions (W x D x H)	431 x 466 x 380 mm
Maximum dimensions (W x D x H)	431 x 1040 x 453 mm
Weight	21.6 kg
Warranty	One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Go to http://www.hp.com/support to learn about HP award winning service and support options in your region