

SPECIFICATIONS

LCD PANEL

Type: 24" W (23.6" Viewable) TN LCD monitor
Display Area: 521.28 (H) x 293.22 (V)
Resolution: Full HD 1920 x 1080
Brightness: 250 cd/m² (Typ)
Contrast Ratio: 1000:1 (Typ)
Dynamic Contrast Ratio: 50,000,000:1
Viewing Angles: 170° (H) / 160° (V) (Typ)
Response Time: 5ms
3ms (GTGavg) in OD
Backlight: 1 WLED light bar
Backlight Life: 20,000 Hrs (Min)
Colours: 16.7M colors (6-bit+Hi-FRC)
Colour Gamut: 72% of NTSC (Typ)
Panel Surface: Anti-Glare type, Hard-coating (3H), Haze 25%

INPUT SIGNAL

Frequency: 24 ~ 82KHz / 50 ~ 75Hz
Sync: Separate Sync

COMPATIBILITY

PC: 1920 x 1080 (Non-Interlaced)
Mac: 1920x1080

CONNECTOR

Digital: HDMI (v1.4) x 1
Analog: VGA x 1
Audio Out (Earphone out): 3.5mm jack x 1

POWER

Power: Internal Power Board
Voltage: AC 100-240V (Universal); 50/60 Hz
Consumption: 20.5W; Optimize: 17.5W (Typ.); Conserve: 14.8W (Typ.)

ERGONOMICS

Tilt: 21°~ -6°

WALL MOUNT

VESA®: 75x75mm

OPERATING CONDITIONS

Temperature: 32°F to 104°F (0°C to 40°C)
Humidity: 20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand: 551.73 (W) x 403.79 (H) x 169.95 (D)

WEIGHT

Net with stand: 3.1kg

REGULATIONS

WEEE, REACH, RoHS, cTUVus, FCC/IC, TUV-MX-CoC, MX-Energy

PACKAGE CONTENTS

LCD Display / Power Cable / D-Sub Video Cable / Quick Start Guide
