

<b>RESOLUTION</b> 3840 x 2160	<b>THROW RATIO</b> 1.13~1.47
<b>THROW DISTANCE</b> 4.9 - 28.8 ft / 1.5 - 8.8 m	<b>BRIGHTNESS (LUMENS)</b> 3,300 ANSI

<b>DISPLAY</b>	
<b>TYPE</b> DLP Laser	<b>RESOLUTION TYPE</b> 4K (3840x2160)
<b>RESOLUTION</b> 3840 x 2160	<b>BRIGHTNESS (LUMENS)</b> 3,300 ANSI
<b>DISPLAY SIZE (IN.)</b> 60 - 300 in. / 1.5 - 7.6 m	<b>THROW DISTANCE</b> 4.9 - 28.8 ft / 1.5 - 8.8 m
<b>THROW RATIO</b> 1.13~1.47	<b>KEystone</b> Vertical (+/- 40°)
<b>LENS</b> 1.3x Manual optical zoom / manual optical focus	<b>LIGHT SOURCE LIFE, NORMAL (HOURS)</b> 20000
<b>LIGHT SOURCE LIFE, DYNAMIC ECO-MODE (HOURS)</b> 20000	<b>COLOR DEPTH</b> 1.07B Color (R/G/B 10bit)
<b>DYNAMIC CONTRAST RATIO</b> 3,000,000:1	<b>ASPECT RATIO</b> 16:9

<b>VIDEO SIGNAL</b>	
<b>FREQUENCY HORIZONTAL</b> 15K~102KHz	<b>FREQUENCY VERTICAL</b> 23~120Hz

<b>COMPATIBILITY</b>	
<b>PC RESOLUTION (MAX)</b> 3840 x 2160	<b>MAC® RESOLUTION (MAX)</b> 3840 x 2160

CONNECTOR	
<b>USB 2.0 TYPE A</b> 1	<b>ETHERNET LAN (RJ45)</b> 1
<b>3.5MM AUDIO OUT</b> 1	<b>3.5MM AUDIO IN</b> 1
<b>CONTROL (RS232)</b> 1	<b>HDMI 1.4 (WITH HDCP 1.4)</b> 1
<b>HDMI 2.0 (WITH HDCP 2.2)</b> 1	<b>VGA IN</b> 2
<b>VGA OUT</b> 1	<b>COMPOSITE RCA VIDEO IN</b> 1
<b>MINI USB</b> 1	

AUDIO	
<b>INTERNAL SPEAKERS</b> 2W (x1)	

POWER	
<b>VOLTAGE</b> 100-240V+/- 10%, 50/60Hz AC	<b>CONSUMPTION (TYPICAL)</b> 260W
<b>STAND-BY</b> <0.5W	

CONTROLS	
<b>PHYSICAL CONTROLS</b> Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source	<b>ON SCREEN DISPLAY</b> Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

OPERATING CONDITIONS	
<b>TEMPERATURE</b> 32-104° F (0 - 40° C)	<b>HUMIDITY (NON-CONDENSING)</b> 0-90%

**ADDITIONAL HARDWARE****KENSINGTON LOCK SLOT**

1

**WEIGHT (IMPERIAL)****NET (LBS)**

15.7

**GROSS (LBS)**

20.1

**WEIGHT (METRIC)****NET (KG)**

7.1

**GROSS (KG)**

9.1

**DIMENSIONS (IMPERIAL) (WXHxD)****PACKAGING (IN.)**

19.7 x 6.2 x 15.8

**PHYSICAL (IN.)**

15.6 x 6.2 x 12.4

**DIMENSIONS (METRIC) (WXHxD)****PACKAGING (MM)**

500.4 x 157.5 x 401.3

**PHYSICAL (MM)**

396.0 x 314.0 x 157.0

**GENERAL****REGULATIONS**

FCC, cTUVus, ROHS

**PACKAGE CONTENTS**

LS700-4K Projector, Power Cable, VGA Cable, Remote Control, Quick Start Guide

**WARRANTY**


Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

**RECYCLE/DISPOSAL**

Please dispose of in accordance with local, state or federal laws.

**DIMENSIONS**

15.6 x 12.4 x 6.2 in / 396.0 x 314.0 x 157.0 mm



01 IR Remote Sensor    02 Projection Lens  
 03 Projection Lens    04 IR Remote Sensor  
 05 Focus/Zoom Rings    06 RS-232  
 07 Computer In    08 AC In  
 09 USB 5V/1.5A Out    10 LAN  
 11 Mini USB    12 Composite