

Specifications

MODEL		PM-UPS1500	PM-UPS2250		
Capacity		1500 VA 900 W	2250 VA 1350 W		
INPUT					
Voltage	100 V / 110 V / 120 V: 80 ~ 150 Vac 220 V / 230 V / 240 V: 162 ~ 295 Vac (220 V: 145 ~ 295 Vac optional)				
Frequency	50 / 60 Hz ± 10% (auto-sense)				
OUTPUT					
Voltage	100 V / 110 V / 120 Vac ± 10% or 220 V / 230 V / 240 Vac ± 10%				
Frequency	50 / 60 Hz ± 1% (auto-sense)				
Waveform	Mains mode: pure sine wave; battery mode: simulated sine wave				
Transfer time	Typical 2 ~ 7 ms; Max. 10 ms				
BATTERIES					
DC voltage	24 V				
Configuration	2X12V/7.0AH	2X12V / 90AH			
Recharge time	6 ~ 8 h				
COMMUNICATIONS					
USB / RS232 / SNMP (optional)	Supports Windows® 98 / 2000 / 2003 / XP / Vista / 2008 / Windows® 7 / 8 / 10				
OTHERS					
Protections	Short circuit – battery overcharge – overdischarge – overload – surge				
Humidity	20 ~ 90% RH @ 0 ~ 40°C (non-condensing)				
Noise level	≤ 45 dB (1m)				
Metal Case	Net / Gross weight (kg)	10.5 / 11.2	14.0 / 14.8		
	Dimensions (W x D x H) (mm)	125 X 320 X 220	125 X 380 X 220		
	Packaged dimensions (W x D x H) (mm)	180 X 390 X 295	180 X 450 X 295		
Output Sockets	2 Universal , Fax/Tel, USB				
Additional					