

RESOLUTION 1920 x 1080	THROW RATIO 0.69-0.83
THROW DISTANCE 3.0 - 7.2 ft / 0.9 - 2.2 m	BRIGHTNESS (LUMENS) 3,000 ANSI

DISPLAY	
TYPE DLP Lamp	RESOLUTION TYPE HD (1920x1080)
RESOLUTION 1920 x 1080	BRIGHTNESS (LUMENS) 3,000 ANSI
DISPLAY SIZE (IN.) 60 - 120 in. / 1.5 - 3.0 m	THROW DISTANCE 3.0 - 7.2 ft / 0.9 - 2.2 m
THROW RATIO 0.69-0.83	KEYSTONE Vertical digital keystone correction ($\pm 20^\circ$)
LENS 1.2x optical zoom	LIGHT SOURCE (WATT) 240
LIGHT SOURCE LIFE, NORMAL (HOURS) 4000	LIGHT SOURCE LIFE, DYNAMIC ECO-MODE (HOURS) 15000
COLOR DEPTH 1.07B Color (R/G/B 10bit)	DYNAMIC CONTRAST RATIO 22,000:1
ASPECT RATIO 16:9	

VIDEO SIGNAL	
FREQUENCY HORIZONTAL 15K~102KHz	FREQUENCY VERTICAL 23~120Hz

COMPATIBILITY	
PC RESOLUTION (MAX) 1920 x 1080	PC RESOLUTION (MIN) 640 x 480
MAC® RESOLUTION (MAX) 1920 x 1080	MAC® RESOLUTION (MIN) 640 x 480

CONNECTOR

USB 3.1 TYPE C 1	3.5MM AUDIO OUT 1
3.5MM AUDIO IN 1	CONTROL (RS232) 1
HDMI 1.4 2	VGA IN 1
COMPOSITE RCA VIDEO IN 1	MINI USB 1

AUDIO

INTERNAL SPEAKERS 5W (x1)

POWER

VOLTAGE 100-240V+/- 10%, 50/60Hz AC	CONSUMPTION (TYPICAL) 310W
STAND-BY <0.5W	

CONTROLS

PHYSICAL CONTROLS Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source	ON SCREEN DISPLAY Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
---	--

OPERATING CONDITIONS

TEMPERATURE 32-104° F (0 - 40° C)	HUMIDITY (NON-CONDENSING) 0-90%
---	---

ADDITIONAL HARDWARE

KENSINGTON LOCK SLOT 1

WEIGHT (IMPERIAL)	
NET (LBS) 6.0	GROSS (LBS) 8.4

WEIGHT (METRIC)	
NET (KG) 2.7	GROSS (KG) 3.8

DIMENSIONS (IMPERIAL) (WXHxD)	
PACKAGING (IN.) 14.4 x 7.4 x 11.8	PHYSICAL (IN.) 11.5 x 4.5 x 8.7

DIMENSIONS (METRIC) (WXHxD)	
PACKAGING (MM) 365.0 188.0 x 300.0	PHYSICAL (MM) 293.0 x 115.0 x 220.0

GENERAL	
REGULATIONS FCC, cTUVus, ROHS	PACKAGE CONTENTS PX706HD projector, power cable, USB Type C cable, remote control, Quick Start Guide
WARRANTY Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).	RECYCLE/DISPOSAL Please dispose of in accordance with local, state or federal laws.

DIMENSIONS

11.5 x 4.5 x 8.7 in / 293.0 x 115.0 x 220.0 mm



01 Menu Controls 02 Elevation Feet 03 Zoom Ring 04 IR Remote Sensor 05 Projection Lens 06 VGA In 07 USB Type-C 08 HDMI (x2)
 09 Audio In 10 Audio Out 11 AC In 12 RS232 13 USB Mini 14 Video 15 Kensington® Lock Slot