

<b>RESOLUTION</b> 1920 x 1080	<b>THROW RATIO</b> 1.5 - 1.65
<b>THROW DISTANCE</b> 2.5 - 25.0 ft / 0.7 - 7.6 m	<b>BRIGHTNESS (LUMENS)</b> 3,500 ANSI

DISPLAY	
<b>TYPE</b> DLP Lamp	<b>RESOLUTION TYPE</b> HD (1920x1080)
<b>RESOLUTION</b> 1920 x 1080	<b>BRIGHTNESS (LUMENS)</b> 3,500 ANSI
<b>DISPLAY SIZE (IN.)</b> 30 - 300 in. / 0.76 - 7.62 m	<b>THROW DISTANCE</b> 2.5 - 25.0 ft / 0.7 - 7.6 m
<b>THROW RATIO</b> 1.5 - 1.65	<b>KEystone</b> Vertical (+/- 40°)
<b>LENS</b> 1.1x optical zoom	<b>LIGHT SOURCE (WATT)</b> 203
<b>LIGHT SOURCE LIFE, NORMAL (HOURS)</b> 5000	<b>LIGHT SOURCE LIFE, DYNAMIC ECO-MODE (HOURS)</b> 15000
<b>COLOR DEPTH</b> 1.07B Color (R/G/B 10bit)	<b>DYNAMIC CONTRAST RATIO</b> 12,000:1
<b>ASPECT RATIO</b> 16:9	

VIDEO SIGNAL	
<b>FREQUENCY HORIZONTAL</b> 15K~102KHz	<b>FREQUENCY VERTICAL</b> 23~120Hz

COMPATIBILITY	
<b>PC RESOLUTION (MAX)</b> 1920 x 1200	<b>PC RESOLUTION (MIN)</b> 640 x 480
<b>MAC® RESOLUTION (MAX)</b> 1920 x 1200	<b>MAC® RESOLUTION (MIN)</b> 640 x 480

CONNECTOR	
<b>USB 2.0 TYPE A</b> 1	<b>3.5MM AUDIO OUT</b> 1
<b>3.5MM AUDIO IN</b> 1	<b>CONTROL (RS232)</b> 1
<b>HDMI</b> 2	<b>VGA IN</b> 1
<b>VGA OUT</b> 1	<b>MINI USB</b> 1

AUDIO	
<b>INTERNAL SPEAKERS</b> 2W (x1)	

POWER	
<b>VOLTAGE</b> 100-240V+/- 10%, 50/60Hz AC	<b>CONSUMPTION (TYPICAL)</b> 350W
<b>STAND-BY</b> <0.5W	

CONTROLS	
<b>PHYSICAL CONTROLS</b> Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source	<b>ON SCREEN DISPLAY</b> Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

OPERATING CONDITIONS	
<b>TEMPERATURE</b> 32-104° F (0 - 40° C)	<b>HUMIDITY (NON-CONDENSING)</b> 0-90%

ADDITIONAL HARDWARE	
<b>KENSINGTON LOCK SLOT</b> 1	

WEIGHT (IMPERIAL)	
<b>NET (LBS)</b> 8.1	<b>GROSS (LBS)</b> 10.8

WEIGHT (METRIC)	
<b>NET (KG)</b> 3.7	<b>GROSS (KG)</b> 4.9


DIMENSIONS (IMPERIAL) (WXHxD)	
<b>PACKAGING (IN.)</b> 16.4 x 8.2 x 13.2	<b>PHYSICAL (IN.)</b> 13.1 x 5.3 x 10.3

DIMENSIONS (METRIC) (WXHxD)	
<b>PACKAGING (MM)</b> 417.0 x 207.0 x 336.0	<b>PHYSICAL (MM)</b> 332.0 x 135.0 x 261.0

GENERAL	
<b>REGULATIONS</b> FCC, cTUVus, ROHS	<b>PACKAGE CONTENTS</b> PX700HD Projector, Power Cable, VGA Cable, Remote Control, Quick Start Guide
<b>WARRANTY</b> Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).	<b>RECYCLE/DISPOSAL</b> Please dispose of in accordance with local, state or federal laws.

### DIMENSIONS

13.1 x 5.3 x 10.3 in / 332.0 x 135.0 x 261.0 mm



01 IR remote sensor    02 Projection lens    03 Elevation foot    04 Focus / zoom rings    05 USB type Mini B    06 USB 2.0 Type A (powered)  
 07 HDMI (x2)    08 AC In    09 VGA    10 RS232    11 Monitor Out    12 Control Panel    13 Kensington® Lock Slot    14 Audio In/Out