

SPECIFICATIONS

SPECIFICATION

Projection system: 0.55" SVGA
Native Resolution: 800x600
DC type: DC3
Brightness: 3600 ANSI lumens
Contrast Ratio with SuperEco mode: 22000:1
Display Color: 1.07 Billion Colors
Light Source: Lamp
Light source life (Nor/SuperEco): 5000/15000
Lamp Watt: 190W
Lens: F=2.56-2.68, f=22-24.1 mm
Projection Offset: 120%+/-5%
Throw Ratio: 1.96~2.15
Image size: 30" - 300"
Throw Distance: 1.19m-13.11m(100" @3.98m)
Keystone: ±40° (Vertical)
Optical Zoom: 1.1x
Audible Noise (Eco): 27dB
Resolution Support: VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility: NTSC, PAL, SECAM
Horizontal Frequency: 15K~102KHz
Vertical Scan Rate: 23~120Hz
Interactive Camera: NA

INPUT

Computer in (share with component): 2
Audio-in (3.5mm): 1

OUTPUT

Monitor out: 1
Audio out (3.5mm): 1
Speaker: 2W

CONTROL

RS232: 1
USB type mini B (Services): 1

OTHERS

Power Supply Voltage: 100-240V+/- 10%, 50/60Hz AC
Power Consumption: Normal: 260W
Standby: <0.5W
Operating Temperature: 0~40°C
Carton: Brown
Net Weight: 2.2kg
Dimensions (WxDxH) w/adjustment foot: 294x218x110mm
Language: English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord: 1
VGA cable: 1

Remote Control: 1
QSG & CD: QSG: 1 / CD: NA

OPTIONAL ACCESSORY

Air Filter: RSPL
