

Getac A140 Specifications

Overview

Operating System:	Windows 10 Professional Windows 7 Professional (Optional downgrade)
Processor:	Intel Core i5-6200U 2.3GHz processor —Turbo Boost Technology up to 2.8GHz —3MB Intel Smart Cache Optional Intel Core i7-6500U 2.5GHz processor —Turbo Boost Technology up to 3.1GHz —4MB Intel Smart Cache Optional Intel Core i5-6300U vPro 2.4GHz processor —Turbo Boost Technology up to 3.0GHz —3MB Intel Smart Cache Optional Intel Core i7-6600U vPro 2.6GHz processor —Turbo Boost Technology up to 3.4GHz —3MB Intel Smart Cache
Storage**:	OPAL 2.0 128GB solid state drive Optional OPAL 2.0 256GB or 512GB solid state drives
Memory:	4GB DDR4* Expandable to 32GB**
Display:	14" TFT LCD (1366x768) 1000 NITs LumiBond™ 2.0 sunlight readable LED display with multi-touch technology (hard-tip stylus) Optional 14" IPS TFT LCD FHD (1920 x 1080) 800 NITs LumiBond™ 2.0 sunlight readable LED display with multi-touch technology (hard-tip stylus)
Communication Interface:	10/100/1000 base-T Ethernet x 2 Intel Dual Band Wireless-AC 8260 (802.11ac) Bluetooth (v4.2) Optional dedicated GPS Optional 4G LTE multi-carrier mobile broadband**
I/O Interface:	DC in x 1 Ethernet x 2 MicroSD USB 3.0 (9-pin) x 2 USB 2.0 (4-pin) x 1 Docking port (24-pin) x 1 Headphone out/Mic-in Combo x 1 HDMI x 1 Optional RF antenna pass-through for GPS, WLAN and WWAN
Expansion Slots:	Optional 1D/2D imager / barcode reader Optional serial port or VGA Optional fingerprint scanner Optional RFID
Keyboard:	Eight tablet buttons: Windows, Power, Camera Capture, Barcode Reader Trigger, OSDC, Rotation Lock, Volume Up, Volume Down
Cameras:	Optional FHD webcam x 1 Optional 8MP auto focus camera
VGA Controller:	Intel HD Graphics 520
Software:	Getac Utility Getac Camera Getac V-GPS Barcode Utility

Security:	<ul style="list-style-type: none"> Intel vPro Technology (per CPU options) TPM 2.0 Cable lock slot NIST BIOS compliant Smartcard reader Optional fingerprint reader Optional contactless smart card reader Optional Absolute™ DDS software TPM 1.2 Cable lock slot NIST BIOS compliant Optional 13.56MHz RFID Optional contactless smart card reader
Power:	<ul style="list-style-type: none"> AC Adapter (65W, 100-240VAC, 50/60Hz) Hot swappable Dual Li-Ion battery (3220mAh) x 2
Dimensions & Weight:	<ul style="list-style-type: none"> 14.53" x 9.76" x 1.28" (369 x 248 x 32.5mm) 5.07lbs (2.3kg)^{††}
Rugged Features:	<ul style="list-style-type: none"> MIL-STD 810G and IP65 certified MIL-STD 461F ready (Requires MIL-STD 461F 90W AC Adapter sold separately.) Optional ANSI/ISA 12.12.01 Vibration & drop resistant
Environmental:	<ul style="list-style-type: none"> Operating Temp: -5.8 °F to 140 °F / -21 °C to 60 °C Storage Temp: -60 °F to 160 °F / -51 °C to 71 °C Humidity: 95% RH, non-condensing
Warranty:	<ul style="list-style-type: none"> 3-year bumper-to-bumper warranty — Protects all major system components and even covers accidental damage!