

Shure KSM32/SL Specs

Microphone

Operating Principle	Pressure Gradient
---------------------	-------------------

Capsule	Condenser
---------	-----------

Polar Pattern	Cardioid
---------------	----------

Pad	-15 dB
-----	--------

Performance

Frequency Range	20 Hz to 20 kHz
-----------------	-----------------

Maximum SPL	139 dB SPL 133 dB SPL
-------------	--------------------------

Impedance	150 Ohms
-----------	----------

Sensitivity	16 mV/Pa
-------------	----------

Dynamic Range	126 dB 119 dB
---------------	------------------

Equivalent Noise Level	13 dB A-Weighted
------------------------	------------------

Connectivity

Output Connectors	1 x 3-Pin XLR
-------------------	---------------

Power

Operating Voltage	48 V \pm 4 V
-------------------	----------------

Operating Current Consumption	4.65 μ A
-------------------------------	--------------

Physical

Length	7.36" / 187 mm
--------	----------------

Diameter	2.20" / 55.9 mm
----------	-----------------

Weight	17.3 oz / 490 g
--------	-----------------

Packaging Info

Package Weight	4.945 lb
----------------	----------

Box Dimensions (LxWxH)	14.55 x 10.4 x 6.5"
------------------------	---------------------
