

Shure BLX24/SM58 Specs

System

Wireless Transmission	Analog UHF
Number of RF Channels	123
Included Transmitters	1 x Handheld
Diversity	Antenna Diversity
RF Frequency Band	J10: 584 to 608 MHz
RF Bandwidth	24 MHz
Max Operating Range	300' / 91.4 m (Line of Sight)
Max Systems per Setup	12
Dynamic Range	100 dBA

Receiver

Form Factor	Table-Top
Antenna	2 x Internal, Fixed

Number of Audio Channels	1
--------------------------	---

Audio I/O	1 x XLR 3-Pin Male Output 1 x 1/4" TRS Female Output
-----------	---

Audio Output Level	XLR Output: -27 dBV (Mic Level) 1/4" Output: -13 dBV (Instrument Level)
--------------------	--

Frequency Response	50 Hz to 15 kHz (Dependent on Mic)
--------------------	------------------------------------

Impedance	XLR Output: 200 Ohms 1/4" Output: 50 Ohms
-----------	--

Approximate RF Sensitivity	-105 dBm
----------------------------	----------

Power Requirements	AC/DC Power Adapter
--------------------	---------------------

AC/DC Power Adapter	12 to 15 VDC at 160 mA, Center-Positive (Included)
---------------------	--

Display & Indicators	1 x Multi-Segment LED (Channel, Group) 2 x LED (AF Level, Sync)
----------------------	--

Housing	ABS
---------	-----

Operating Temperature	0 to 135°F / -17 to 57°C
-----------------------	--------------------------

Dimensions	7.4 x 1.6 x 4.1" / 188.0 x 40.0 x 103.0 mm
------------	--

Weight	8.5 oz / 241.0 g
--------	------------------

Transmitter

Form Factor	Handheld
-------------	----------

RF Output Power	10 mW
-----------------	-------

Audio I/O	<i>None</i>
-----------	-------------

Muting	Off/On Switch
--------	---------------

Gain Range	-20 to -10 dB
------------	---------------

Sync Method	Manual
-------------	--------

Antenna	1 x Internal (Handheld)
---------	--------------------------------

Power Requirements	Battery
--------------------	---------

Battery Type	2 x AA (Included)
--------------	--------------------------

Approx. Battery Life	14 Hours (Alkaline)
----------------------	---------------------

Display & Indicators	1 x Multi-Segment LED (Channel, Group) 1 x LED (Battery Status, Power)
----------------------	---

Housing	ABS
Dimensions	2.5 x 4.3 x 0.8" / 64.0 x 110.0 x 21.0 mm
Weight	7.7 oz / 218.0 g (without Batteries)

Microphone

Form Factor	Handheld Capsule
Sound Field	Mono
Transducer	Dynamic
Polar Pattern	Cardioid
Frequency Range	50 Hz to 15 kHz
Sensitivity	-54.5 dBV/Pa at 1 kHz

Packaging Info

Package Weight	4.4 lb
Box Dimensions (LxWxH)	18.2 x 13 x 4.3"