

<b>Printing Technology</b>	Direct Thermal
<b>Print Speed (maximum)</b>	6 inches per second (150 mm/s)
<b>Print Width (maximum)</b>	4 inches (104 mm)
<b>Media Width (min to max)</b>	0.5 to 4 inches (12.5 to 118 mm)
<b>Media Thickness (min to max)</b>	63.5 to 254 µm
<b>Media Sensor</b>	Fully adjustable gap, notch and reflective black mark
<b>Media Length (min to max)</b>	0.25 to 64 inches (6.35 to 1625.6 mm)
<b>Roll Size (max), Core Size</b>	Inside diameter 5 inches (125 mm) External diameter 8 inches (200mm) Core size 1 inch (25mm)
<b>Case</b>	Hi-Open™ industrial ABS case with safe close
<b>Mechanism</b>	Hi-Lift™ metal mechanism with wide opening head
<b>Control panel</b>	4 buttons and 4 LEDs
<b>Flash (Non-Volatile Memory)</b>	4 MB total, 1 MB available for user
<b>Drivers and software</b>	Free-of-charge on CD with printer, including support for various platforms
<b>Size (W x D x H) and Weight</b>	231 x 289 x 183mm, 3.6 Kg
<b>Warranty</b>	2 years on printer. 6 months or 30 Kms on printhead

<b>Emulations (Languages)</b>	Datamax® I-Class™ & DMX400™ Zebra® ZPL-II® Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400 BASIC interpreter for data stream processing
<b>RAM (standard Memory)</b>	16 MB total, 1 MB available for user
<b>Resolution</b>	203 dpi
<b>Main Interface</b>	Dual Interface Serial (RS-232C), USB (version 2.0, full speed)
<b>Interface</b>	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps Ethernet (10/100 BaseT) Parallel (IEEE 1284 compliant)