

Printing Technology	Thermal Transfer + Direct Thermal
Print Speed (maximum)	4 inches per second (100 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	0.5 to 4 inches (12.5 to 118 mm)
Media Thickness (min to max)	63.5 to 254 µm
Media Sensor	Fully adjustable gap, notch and reflective black mark
Media Length (min to max)	0.25 to 64 inches (6.35 to 1625.6 mm)
Roll Size (max), Core Size	Inside diameter 5 inches (125 mm) External diameter 8 inches (200mm) Core size 1 inch (25mm)
Case	Hi-Open™ industrial ABS case with safe close
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons and 4 LEDs
Flash (Non-Volatile Memory)	4 MB total, 1 MB available for user
Drivers and software	Free-of-charge on CD with printer, including support for various platforms
Size (W x D x H) and Weight	231 x 289 x 270 mm, 4.5 Kg
Warranty	2 years on printer. 6 months or 50 Kms printhead

Emulations (Languages)	Datamax® I-Class™ & DMX400™ Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400 Zebra® ZPL-II® BASIC interpreter for data stream processing
Ribbon size	2.9 inches (74mm) maximum outside diameter. 360 metres length. 1 inch (25mm) core
Ribbon winding & type	Ink side in or out, switch selectable. Wax, Wax/Resin or Resin Type
Ribbon system	ARCP™ automatic ribbon tension adjustment
RAM (standard Memory)	16 MB total, 1 MB available for user
Resolution	203 dpi
Main Interface	Dual Interface Serial (RS-232C), USB (version 1.1)
Interface	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps Ethernet (10/100 BaseT) Parallel (IEEE 1284 compliant)