

Printing Technology	Thermal Transfer + Direct Thermal
Print Speed (maximum)	8 inches per second (200 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	0.5 to 4 inches (12.5 to 118 mm)
Media Thickness (min to max)	63.5 to 254 µm
Media Sensor	Fully adjustable gap, reflective black mark and ribbon near end
Media Length (min to max)	0.25 to 158 inches (6.4 to 4013 mm, depending on emulation)
Roll Size (max), Core Size	Outside diameter 8 inches (200mm) Core size 1 to 3 inches (25 to 75 mm)
Case	Hi-Open™ metal case with safe, soft-close feature
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons, 2-colour backlit graphic LCD with status LED
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user
Drivers and software	Free-of-charge on CD with printer, including support for various platforms
Size (W x D x H) and Weight	250 x 458 x 261 mm, 11 Kg
Warranty	2 years on printer. 6 months or 50 Kms printhead

Emulations (Languages)	Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400
Ribbon size	2.9 inches (74mm) maximum outside diameter. 360 metres length. 1 inch (25mm) core
Ribbon winding & type	Ink side in or out, automatically sensing. Wax, Wax/Resin or Resin Type
Ribbon system	ARCP™ automatic ribbon tension adjustment
RAM (standard Memory)	32MB total, 4 MB available for user
Power consumption	230V: 65W (operating at 6 IPS at 12.5% printing duty), 2.6W (standby)
Resolution	203 dpi
Main Interface	Triple interface: USB and Ethernet built-in plus interface card slot for optional card
Interface	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps Premium Wireless LAN Ethernet (10/100 BaseT) Ethernet (SEH) Serial (RS-232C compliant) Parallel (IEEE 1284 compliant)