

Detailed Tech Specification

General

Display Type Diagonal Size

D-backlit LCD monitor / TFT active matrix 20"

Panel Size Built-in Devices

5" USB 3.0 hub

Panel Type Aspect Ratio

16:9

Native Resolution Pixel Per Inch

1920 x 900 at 60 Hz 94

Brightness Contrast Ratio

300 cd/m² 1000:1 / 4000000:1 (dynamic)

Colour Support Response Time

16.7 million colours 5 ms (black-to-white)

Vertical Refresh Rate Horizontal Refresh Rate

50 – 76 Hz 30 – 83 kHz

Horizontal Viewing Angle Vertical Viewing Angle

178° 160°

Screen Coating Backlight Technology

Anti-glare, 3H Hard Coating WLED

Features

99% (CIE 1931) colour gamut, 84% (CIE 1976) colour gamut, PowerNap, stand lock, Flicker-free technology, BFR/PVC-free, Energy Gauge, Dell ComfortView

Dimensions (WxDxH)

15 cm x 18 cm x 33.88 cm – with stand

Weight

1.8 kg

Connectivity

Interfaces

DisplayPort

HDMI

VGA

2 x USB 2.0 downstream

1 x USB 3.0 upstream

2 x USB 3.0 downstream

Mechanical

Display Position Adjustments Tilt Angle

Height, pivot (rotation), swivel, tilt-5/+21

Swivel Angle Rotation Angle

90°

Height Adjustment Flat Panel Mount Interface

100 mm 100 x 100 mm

Miscellaneous

Features

Security lock slot (cable lock sold separately), VESA interface support

Accessories Included

1 x SuperSpeed USB cable

1 x VGA cable

1 x DisplayPort cable

Compliant Standards

CP, CEL, TCO Displays, TUV Rheinland Low Blue Light Certification

Power

Voltage Required Power Consumption Operational

120/230 V (50/60 Hz) 14 Watt

Power Consumption Stand by Power Consumption (Off Mode)

Watt 0.3 Watt

Software / System Requirements

Included Software

Drivers & Utilities

Dimensions & Weight

Dimensions & Weight Details

With stand – width: 46.15 cm – depth: 18 cm – height: 33.88 cm – weight: 4.3 kg

Without stand – width: 46.15 cm – depth: 5.01 cm – height: 27.32 cm – weight: 2.4 kg

Dimensions & Weight (Shipping)

Shipping Weight

3 kg

Environmental Standards

ENERGY STAR Certified

3

Manufacturer Warranty

Service & Support

Limited warranty – 1 years

Standard Services

3 years Advanced Exchange Service and Premium Panel Guarantee

Environmental Parameters

Operating Temperature Max Operating Temperature

0 °C 40 °C

Humidity Range Operating

– 80% (non-condensing)