

- **Audio**
    - **Analog Output:** 2.0 Vrms (0 dBFS, 1 kHz)
    - **Dynamic Range:** 116 dB
    - **Distortion (THD+N):** < 0.0015%
    - **Frequency Range:** 22–22,000 Hz
    - **Digital Output:**
      - Sampling Rate: 96 kHz
      - Bit Depth: 24-bit
- 

- **Motor**
    - **Drive:** Brushless DC Electric
    - **High Torque:** 3.3 kgf/cm (instant); 2.8 kgf/cm (stable)
    - **Low Torque:** 1.6 kgf/cm (instant); 1.1 kgf/cm (stable)
    - **Starting Time:** 0.5 seconds
    - **Braking System:** Electronic
- 

- **Platter**
    - **Material:** Aluminum die-cast
    - **Diameter:**  $\phi$  203.5mm  $\pm$ 0.5mm
    - **Weight:** 900g  $\pm$ 5%
- 

- **Display**
    - 7.0" / 178 mm (diagonal)
    - 6.0" x 3.6" / 152 x 91 mm (width x height)
    - Full-color LED-backlit display with touchinterface
- 

- **Connections**
    - (2) RCA output pairs
    - (2) coaxial digital outputs
    - (1) 1/8" (3.5 mm) mini TS input (remote start)
    - (3) USB Type-A ports (for USB drives) (Rear-panel ports supply 900mA for USB 3.0 devices, 500 mA for USB 2.0 devices. Frontpanelport supplies 500 mA for USB 2.0 devices only.)
    - (1) USB Type-B port (for computer connection)
    - (1) SD card slot
    - (1) Ethernet link port
    - (1) IEC power input
- 

- **Power**
    - **Connection:** IEC
    - **Input Voltage:** 110–240 VAC, 50/60 Hz
-

- **Dimensions (Width x Depth x Height)**

- 320mm X 419mm X 135mm

- 12.6" x 16.5" x 5.3"

- 32.0 x 41.9 x 13.5 cm

---

- **Weight (Without USB and Power Cable)**

- 14.08 lbs.

- 6.4 kg

---

- **Supported Media**

- **Type:**

- SD/SDHC card

- USB mass-storage devices (flash memory, external HDD enclosures)

- **File Systems:**

- exFAT

- FAT32 (recommended)

- **File Formats:**

- AAC/M4A

- AIF/AIFF (44.1–192 kHz, 16–32-bit)

- ALAC

- FLAC

- MP3 (32–320 kbps, VBR)

- MP4

- Ogg Vorbis

- WAV (44.1–192 kHz, 16–32-bit)