

- **Frequency response**
    - **20Hz to 20kHz:** +/-1dB
- 

- **Dynamic Range**
    - **A-weighted:** > 108dB
- 

- **Signal to Noise Ratio**
    - **A-weighted:** > 88dB
- 

- **Headroom**
    - **LINE Input:** > 18dB
    - **MIC Input:** > 20dB
    - **Outputs:** > 20dB
- 

- **Mic Input EIN**
    - **Rs = 150ohm, DIN:** < -119dBu
- 

- **Mic Input CMRR**
    - **1kHz, unity:** > 80dB
- 

- **Channel separation**
    - **1kHz, unity:** < -105dB
- 

- **T.H.D**
    - **1kHz, unity LINE/PHONO:** < 0.01%
    - **1kHz, unity MIC:** < 0.02%
- 

- **Analog input**
    - **MIC Unity:** -40dBu
    - **MIC Minimum:** -60dBu
    - **LINE Maximum:** +18dBV
    - **LINE Unity:** 0dBV
- 

- **Analog output**
    - **Master Balanced Maximum:** +24dBu
    - **Master Balanced Unity:** +4dBu
    - **Master Unbalanced Maximum:** +20dBu
    - **Master Unbalanced Unity:** 0dBu
    - **Booth Maximum:** +24dBu
    - **Booth Unity:** +4dBu
    - **Headphone Output:** > 150mW @40ohm
-

- **Unit Weight**
    - 7kg (without USB cable and adaptor)
- 

- **Unit Dimensions (Width x Depth x Height)**
    - 664mm X 378.2mm X 68.2mm
- 

- **Total Power Consumption**
  - 15w