

- **Frequency response**
 - **20Hz to 20kHz:** +/-1dB

- **Dynamic Range**
 - **A-weighted:** > 108dB

- **Signal to Noise Ratio**
 - **A-weighted:** > 88dB

- **Headroom**
 - **LINE Input:** > 18dB
 - **MIC Input:** > 20dB
 - **Outputs:** > 20dB

- **Mic Input EIN**
 - **Rs = 150ohm, DIN:** < -119dBu

- **Mic Input CMRR**
 - **1kHz, unity:** > 80dB

- **Channel separation**
 - **1kHz, unity:** < -110dB

- **T.H.D**
 - **1kHz, unity LINE/PHONO:** < 0.01%
 - **1kHz, unity MIC:** < 0.05%

- **Analog input**
 - **MIC Unity:** -40dBu
 - **MIC Minimum:** -60dBu
 - **LINE Maximum:** +18dBV
 - **LINE Unity:** 0dBV

- **Analog output**
 - **Master Balanced Maximum:** +24dBu
 - **Master Balanced Unity:** +4dBu
 - **Master Unbalanced Maximum:** +20dBu
 - **Master Unbalanced Unity:** 0dBu
 - **Booth Maximum:** +24dBu

- **Dimensions & Weight (Unit)**

- 2.39 (W) x 1.42 (D) x 0.23 (H) in feet
 - 28.68 (W) x 17.04 (D) x 2.76 (H) in inches
 - 728.47 (W) x 432.82 (D) x 70.10 (H) in mm
 - 8.34 kg
 - 18.39 lbs.
-

- **Dimensions & Weight (Giftbox & Unit)**

- 2.84 (W) x 1.76 (D) x 0.43 (H) in feet
- 34.08 (W) x 21.12 (D) x 5.16 (H) in inches
- 865.63 (W) x 536.45 (D) x 131.06 (H) in mm
- 10.71 kg
- 23.61 lbs.